

HP PS/2 Slim Business Keyboard (N3R86AA)



Full-speed productivity

Get fast data entry and legacy compatibility with your environment with the HP PS/2 Business Slim Keyboard, designed to complement the 2015 class of HP Business PCs.

Multi-OS compatibility

Interact seamlessly with a full-sized keyboard layout that's optimized for use with multiple operating systems.¹

Legacy connectivity

Easily connect the keyboard to any PS/2 keyboard port on your PC.

Rest easy

Get the reassurance of a one-year limited warranty.

¹ See product QuickSpecs for compatible operating systems.

HP PS/2 Slim Business Keyboard

Model number	N3R86AA		
Physical Characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)	
	Dimensions (L x W x H)	171.97 x 68.35 x 8.27 in (436.8± 1.5 x 137.6± 1.0 x 21.0± 1.0 cm)	
	Weight	1.32 lb (600± 80 g)	
Electrical	Operating voltage	+ 4.4 – 5.25VDC	
	Power consumption	50-mA maximum (with 5 VDC power supplied and three LEDs ON)	
	System interface	PS/2 6-pin mini din connector	
	ESD	Contact Discharge: 2, 4,6,8KV	
	Air Discharge:	2, 4, 8,10,12.5KV	
	EMI - RFI	Conforms to FCC rules for a Class B computing device	
	Microsoft PC 99 - 2001	Functionally compliant	
	Keycaps	Low-profile design	
	Switch actuation	60±12.5g nominal peak force with tactile feedback	
	Switch life	10 million keystrokes (Life tester)	
	Switch type	Contamination-resistant switch membrane	
	Key-leveling mechanisms	For all double-wide and greater-length keys	
	Cable length	6 ft (1.8 m)	
	Microsoft PC 99 - 2001	Mechanically compliant	
	Environmental	Acoustics	43-dBA maximum sound pressure level
		Operating temperature	50° to 122° F (10° to 50° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
Operating humidity		10% to 90% (non-condensing at ambient)	
Non-operating humidity		20% to 80% (non-condensing at ambient)	
Operating shock		N/A	
Non-operating shock		65 inch 2.9 ms, six surface; 30g 266 inch/second; 50g 266 inch/second six surface	
Operating vibration		2-g peak acceleration	
Non-operating vibration		Starting at 5 Hz, vary the frequency of vibration from 5 to 500 Hz and back to 5 Hz at a Logarithmic sweep rate of 1 octave per minute.	
Drop (out of box)		26 in (66 cm) on carpet, six-drop sequence	
Drop (in box)		29.93 in (76 cm) on concrete, 16-drop sequence	
Approvals	UL, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC		
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS		

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

